



FEELIS USA, INC.

333 N. Berry St. Brea, CA 92821 U.S.A.
 Phone : 714 523 2146 / Fax : 714 523 2147 / E-mail : lewis@feelisusa.com
 Website : <http://www.feelisusa.com>

LED Light Board (Dynamic White Type)

Technical Information

Thickness	5/16" (8mm)
Light Guide Panel	1/4" (6mm) Acrylic with V cut
Minimum Size	2" W x 2" L (50mm W x 50mm L)
Maximum Size	60" W x 118" L (1,500mm W x 3,000mm L)
Heat Sinking	By aluminum channel
Safety Design	Plastic corner pieces for sharp corner & cable protection (U.S. Patented)
Mounting	By double sided tape, standoffs, Z clips or others
Weight	1.65 lbs / sq ft (7.64 Kg / sq meter)
Input Voltage	D.C. 12 Volt or 24 Volt
LED	One(1) edge, two(2) edges, three(3) edges or four(4) edges
Color Temperature	Controllable Color Temperature (2700K ~ 6500K)
Color Temperature Control	By wireless remote controller (Optional), built-in step controller (Optional), or by others
Dimming Control	By wireless remote controller (Optional), or by others
Power Consumption	4.0 Watt / ft of LED (12 Watt / meter of LED)
Power Cord	22 AWG, 3 conductors cable for wireless remote controller type 20 AWG with barrel type connector for built-in step controller type Length of cord : Standard : 5' (1,500mm), Optional : 10' (3,000mm)
Power Supply	UL class 2 or LPS D.C. 12 Volt : Max. 4.86 Amp / 58.5 Watt D.C. 24 Volt : Max. 3.77 Amp / 90.9 Watt or CE approved
Operating Temperature	-22°F (-30°C) ~ 104°F (+40°C)
Environment	Suitable for indoor and dry location
Certification	UL listed (E344086) UL recognized (E341820) CE approved
Optional	Diffuser plate

Brightness

Dimension (Inch)	Dimension (mm)	LED	Surface Brightness (Lux)	Power Consumption (W)
6" x 12"	152 x 304	1 long side	7,000	3.0
12" x 12"	304 x 304	1 long side	3,500	3.0
18" x 24"	457 x 609	2 long sides	5,000	13.2
24" x 36"	609 x 914	2 long sides	3,600	20.4
36" x 72"	914 x 1828	2 long sides	2,500	43.3
48" x 96"	1219 x 2438	2 long sides	2,000	56.4
60" x 118"	1500 x 3000	4 sides	2,000	98.0